PROJECT DETAILS



ENERGY SAVING AEROSTRIP® DIFFUSERS FOR BUNBURY WWTP



AEROSTRIP[®] Membrane Diffuser technology was developed to provide the most energy efficient process for providing oxygen to aerated biological processes.

Water Corporation's Bunbury WWTP recently underwent an upgrade to replace some older assets within the site and increase plant capacity.

The process includes a fine screen facility, grit removal, 4 x SBRs, sludge plant and effluent disinfection.

Over 2000 AEROSTRIP[®] diffusers were delivered to be fitted to the four SBR reactors. The AEROSTRIP[®] units were fitted to removable frames to enable lift out for inspection purposes.



Hydroflux worked with Water Corporation to enable a cost benefit analysis across multiple diffuser floor

Item	Value
Plant Capacity	13 MLD
Number of Diffusers	2288
Diffuser Length	3M
Process Type	SBR
Bubble Size	1mm
Material	Polyurethane membrane

densities, air flow, energy consumption and subsequent life cycle costs.

The installation shows that increasing floor density can provide a life cycle benefit when both the capital and operating costs are taken into consideration.

The unique micro perforations provide a 1mm bubble size, which in turn maximises mass transfer efficiency of oxygen.

SAE's of 4.5—5.5 kg O₂/kW are achieved with AEROSTRIP[®] diffusers and both clean water and off gas tests have demonstrated this performance and new and existing installations.

Some of Australia's largest treatment plants have now installed AEROSTRIP[®] diffusers, with enough energy savings over conventional circular disc units to power thousands of houses.

Level 26, 44 Market Street Sydney, NSW 2000 www.hydrofluxepco.com.au e: info@hydrofluxepco.com.au

1300 417 697

EXCLUSIVE AGENTS FOR



AEROSTRIP®





